



GC GREASE 00

Soft grease for central lubrication

Lithium

NLGI 00 – Extreme-pressure

TYPE OF USE

Grease specially formulated for central lubrication fitted on trucks, civil engineering machinery and agriculture machinery.

Temperatures for use : from -50°C / -58°F to +120°C / +248°F.

PERFORMANCE

Soft grease formulated with lithium soap and extreme-pressure, anti-rust & anti-oxidation additivation.

Complies with WILLY VOGEL requirements.

Good properties under heavy loads.

Very good cold flow properties for better grease circulation in the pipes at cold temperature.

Water resistant.

Anti-corrosion.

Anti-rust.

Anti-oxidation.

Excellent anti-wear properties.

Designation DIN 51502 : MP 00/000 K-50

PROPERTIES

Color	Visual	Red
Consistency grade	DIN 51 818	NLGI 00/000
Soap		Lithium
Penetrability - 60 cycles	ASTM D217	400 / 460 x10 ⁻¹ mm
Drop point	ASTM D2265	>160°C / >320°F
Anti-corrosion EMCOR	IP 220	0 / 0
4 ball Test	ASTM D2596	2200 N

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL. 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – Tel : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79 - Web Site: www.motul.fr

07/09