



ROULEMENT PL

Solid grease for truck wheel hub

Lithium

NLGI 3 – Extreme Pressure

TYPE OF USE

NLGI 3 consistency grease specially recommended for the greasing of truck wheel hubs. This product can also be used for other applications, in the industry for example.

Temperature for use : from -20°C / -4°F to +130°C / +266°F.

PERFORMANCE

Grease formulated with mineral base oil stocks, with lithium soap and with extreme-pressure, anti-wear & anti-oxidation additivation.

Its very complete additivation allows resisting to extreme pressures and very strongly sticking on surfaces while keeping all its properties over a very long period.

Anti-corrosion. Anti-rust. Anti-oxidation.

Designation DIN 51502 : KP 3 K-20

PROPERTIES

Color	Visual	Light Brown
Consistency grade	DIN 51 818	NLGI 3
Soap		Lithium
Penetrability - 60 cycles	ASTM D217	220 / 250 x10 ⁻¹ mm
Drop point	ASTM D2265	190°C / 374°F
Anti-corrosion EMCOR	IP 220	0 / 0
TIMKEN Test - Load	ASTM D2509	45 lb
FAG FE-9 Test	DIN 51 821	F50 > 100 hr at 130°C (266 °F)

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL. 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – Tel : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79 - Web Site: www.motul.fr