



GEAR Competition 75W-140

**Racing lubricant for limited slip differential
integrated in the gearbox or not.**

100% Synthetic – Ester based

TYPE OF USE

Specially designed for racing vehicle gearboxes : speed way, rally, raid...
All hypoid differentials with limited slip system, gearbox with integrated limited slip differential, mechanical transmission, synchronized or not synchronized gearboxes, transfer gearboxes operating under shocks, heavy loads and low revolution speed or moderate loads and high revolution speed.

PERFORMANCES

STANDARDS Above Existing Standards
SPECIFICATIONS API GL5 – MUGEN Le Mans 24H – HEWLAND and X-TRAC Japanese GT

100% synthetic extreme pressure lubricant for an efficient anti-wear protection, a better resistance at high temperature and a longer life time.

Included friction modifier avoid noisy or dragging limited slip differential.

0% shear loss : Unshearable oil film in extreme conditions.

Stays in 140 grade after KRL 20 hours shear test as requested by SAE J306 Standard, July 1998 update

Very high lubricating power which decreases friction and wear.

140 grade at hot temperature to provide outstanding oil film resistance at hot temperature and/or to reduce transmission noise.

Fluid at low temperature to allow easier gear shifting when the gearbox is cold.

Less effort required on the gear lever to shift the gears.

Suitable for any type of seal and yellow material used in gearboxes design.

Anti-corrosion, Anti-foam.

RECOMMENDATIONS

Oil change: According to manufacturers' requirements and adjust according to your own use.

PROPERTIES

Color	Visual	Blue
Viscosity grade	SAE J306	75W-140
Density at 20°C (68°F)	ASTM D1298	0.903
Viscosity at 40°C (104°F)	ASTM D445	170 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	24.7 mm ² /s
Viscosity index	ASTM D2270	178
Flash point	ASTM D92	212°C / 413°F
Pour point	ASTM D97	-36°C / -33°F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79 - Web Site : www.motul.fr

09/10