



# SELLETTE

**Grease for semi-trailer fifth wheels**

**Anti-seizing**

**NLGI 2 – Graphite**

## TYPE OF USE

Grease specially formulated for the lubricating of semi-trailer fifth wheels.

Can be also used for the greasing of cables, open gears, ring gears, gear-racks and ball joints for civil engineering machinery.

Temperature for use : from -30°C / -22°F to +140°C / +284°F.

## PERFORMANCE

Extreme-pressure grease based on lithium soap and reinforced with graphite. Adhesive.

Very sticky.

Very good resistance to water.

Anti-corrosion, anti-rust protection.

Designation DIN 51502 : KPF 2 N-30

## PROPERTIES

Color	Visual	Black
Consistency grade	DIN 51 818	NLGI 2
Soap		Lithium
Penetrability - 60 cycles	ASTM D217	265 / 295 x10 <sup>-1</sup> mm
Drop point	ASTM D2265	190°C / 374°F
Anti-corrosion EMCOR	IP 220	0 / 0
4 ball Test	ASTM D2596	3200 N

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL. 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – Tel : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79 - Web Site: [www.motul.fr](http://www.motul.fr)

07/09