



H-TECH 100 Plus 5W-30

Fuel Economy Gasoline Engine Lubricant

100% Synthetic

TYPE OF USE

Designed for fuel economy performance and provide ultimate level of power especially for recent gasoline engine designs.

Suitable for turbo or naturally aspirated gasoline engines, equipped with catalytic converters.

Suitable for all gasoline engines using leaded or unleaded gasoline, LPG, Autogas fuel.

All driving conditions : City, Road, Highway.

PERFORMANCE

STANDARD ILSAC GF-5
 API SN

Designed to meet the new ILSAC GF-5 and API SN specifications. Provides exceptional engine protection and at the same time even more efficient operation. Improved fuel economy and greater power when compared to more viscous products.

Formulated with latest technology to ensure emission control systems durability. The high performance anti-wear additive results in reduction of engine internal frictions and increases engine life duration by reducing wear.

Excellent anti-oxidation preventing premature oil thickening and ageing due to thermal stress.

Very efficient anti-deposit and anti-black sludge power which maintains a clean engine.

Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Drain period : according to manufacturers' recommendations and driving patterns.

PROPERTIES

Viscosity grade	SAE J 300	5W-30
Density at 15°C (59°F)	ASTM D1298	0.849
Viscosity at 100°C (212°F)	ASTM D445	10.1 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	58.9 mm ² /s
Viscosity index	ASTM D2270	160
TBN	ASTM D2896	6.1 mg KOH/g