



HONDA HR LUB 4T 10W-30

4 Stroke engine Lubricant for Honda engines

Gasoline Engines

Technosynthèse

TYPE OF USE

Specially formulated for Honda motorised gardening tools and small farming machines
All Gasoline 4 Stroke engines: Lawn mowers, motor mowers, grass cutters, light tractors, power generators, power pumps, blowers...
Suitable for all types of fuel : leaded and unleaded gasoline.
All types of 4 stroke engines with or without catalytic converter.

PERFORMANCE

STANDARDS : **API SL / CF**

Reinforced with a synthetic base stock for improved engine protection
Dispersant and detergent properties ensure better engine cleanliness, avoids ring sticking, avoid deposits and varnishes on valves and piston. Minimize black sludge in oil sump.
Anti-corrosion properties for a better protection during wintering
10W-30 viscosity grade ensures easy cold starting and perfect stability at hot temperature.
Anti-oxidation, Anti-wear, Anti-foam properties.

RECOMMENDATIONS

Oil change: According to Honda's requirements : every 6 months or every 50 hours.
MOTUL HONDA HR LUB 4T SAE 10W-30 can be mixed with synthetic or mineral lubricants.

PROPERTIES

Viscosity grade	SAE J 300	10W-30
Density at 20°C (68°F)	ASTM D1298	0.870
Viscosity at 40°C (104°F)	ASTM D 445	66.3 mm ² /s
Viscosity at 100°C (212°F)	ASTM D 445	10.6 mm ² /s
Viscosity index (VIE)	ASTM D 2270	149
Flash point	ASTM D 92	226°C / 439°F
Pour point	ASTM D 97	-30°C / -22°F
TBN	ASTM D2896	8.0 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79 - Site Web : www.motul.fr

09/10