



# KART 4T 10W-40

Lubricant for 4 stroke Go-kart engines

## Technosynthese

### TYPE OF USE

Especially developed for rental Go-kart fleet fitted with 4 stroke engines with centrifugal clutch or integrated gearbox with wet clutch.

### PERFORMANCES

STANDARDS:                **API SJ / SH / SG**  
APPROVAL:                **JASO MA**

Technosynthese lubricant: Engine cleanliness and oil film resistance are increased for intensive "Stop & Go" or endurance use.

The API SJ specification offers a higher level of detergency and better oxidation stability allowing "stay in grade" viscosity between drain intervals.

Engine is well protected and can run at high revs under heavy load.

JASO MA to ensure perfect wet clutch locking at start-up, acceleration and full speed.

### RECOMMENDATIONS

Oil change: according to manufacturers' requirements and to be adjusted according to particular use.  
Can be mixed with synthetic or mineral lubricants.

### PROPERTIES

Viscosity grade	SAE J 300	<b>10W-40</b>
Density at 20°C (68°F)	ASTM D1298	0.870
Viscosity at 40°C (104°F)	ASTM D445	100.5 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	15.14 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	157
Pour point	ASTM D97	-43°C / -45.4
Flash point	ASTM D92	210°C/ 410°F
TBN	ASTM D2896	8 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. Made in France

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79 - Website : [www.motul.fr](http://www.motul.fr)

05/10