



LHM Plus

Mineral fluid for CITROEN hydraulic systems

TYPE OF USE

Mineral fluid for the lubrication of hydropneumatic suspension and braking systems, green-painted, of CITROEN vehicles only (since 1966).

PERFORMANCES

SPECIFICATION : CITROEN.

Improved performance at low temperature over classic LHM.

Extreme stability.

Anti-corrosion.

Anti-foam.

Anti-wear.

RECOMMENDATIONS

To be used only in green-painted hydraulic circuits designed by CITROEN.

Not to be used in black-painted hydraulic circuits.

Not to be mixed with synthetic or other fluids.

PROPERTIES

Coloured in green.

Density at 20°C (68°F)	ASTM D1298	0.830
Viscosity at 100°C (212°F)	ASTM D445	6.1 mm ² /s
Viscosity at -40°C (- 40°F)	ASTM D2602	1056 mm ² /s
Viscosity index	ASTM D2270	335
Flash point	ASTM D92	115°C / 239°F
Pour point	ASTM D97	-60°C / -76°F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - TEL : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79 - Web Site : www.motul.fr

09/10