



Micro 2T

2 Stroke engine lubricant for RC vehicles

100% Synthetic

Miscible with methanol

TYPE OF USE

100% Synthetic lubricant specially formulated for 2 Stroke engines RC – Radio Controlled vehicles: RC cars, boats, planes, etc...
Entirely miscible with nitromethane, methanol, ether...

PERFORMANCE

Highly resistant to mechanical efforts, it avoids sticking.
Keeps the engine clean (no deposits).
Very stable during storage and cold weather.
Miscible with nitromethane, methanol and ether.
Anti-corrosion. Anti-rust.

RECOMMENDATIONS

MOTUL MICRO 2T can be mixed with methanol, nitromethane or ether according to the following proportions (15 to 20% depending on the use and manufacturer's recommendations):

MOTUL MICRO 2T	15 - 20%
METHANOL	70 - 75%
NITROMETHANE	10%

To be adjusted according to your own use or experience.

PROPERTIES

Color	Visual	Red
Density at 20°C (68°F)	ASTM D1298	0.993
Viscosity at 40°C (104°F)	ASTM D445	180 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	31.8 mm ² /s
Viscosity Index	ASTM D2270	213
Flash point	ASTM D92	225°C / 437°F
Pour point	ASTM D97	-30°C / -22°F