



# MULTIGREASE 150

**Multipurpose Grease**

**Lithium**

**NLGI 2 – Extreme Pressure**

## TYPE OF USE

Multipurpose grease for roller bearings, articulations, bearings, hubs, ball joint, water pumps...  
Car, Motorbike, Marine, Transport, Civil engineering machinery, Industry and Farm machines...

Temperature for use : from -30°C / -22°F to +130°C / +266°F.

## PERFORMANCE

Multipurpose grease formulated with lithium soap, mineral base oil stock and with dedicated extreme-pressure, anti-wear, anti-oxidation & anti-corrosion additivation.

Good adherence to metal.

Good resistance to load.

Resistant to water.

Good anti-corrosion and anti-rust protection.

Good mechanical stability.

Designation DIN 51502 : KP 2 K-30

## PROPERTIES

Color	Visual	Brown
Consistency grade	DIN 51 818	NLGI 2
Soap		Lithium
Penetrability - 60 cycles	ASTM D217	265 / 295 x10 <sup>-1</sup> mm
Drop point	ASTM D2265	180°C / 356°F
Anti-corrosion EMCOR	IP 220	0 / 0
TIMKEN Test - Load	ASTM D2509	40 lb
FAG FE-9 Test	DIN 51 821	F50 > 100 hr at 130°C (266 °F)

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL. 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – Tel : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79 - Web Site: www.motul.fr

07/09