



MULTIPOWER 15W-50

Gasoline and Diesel Engine Oil

Technosynthèse^â

TYPE OF USE

Designed for passenger cars equipped with gasoline or Diesel engines, turbo or naturally aspirated.

Suitable for standard and unleaded fuel.
All driving conditions : City, Road, Highway.

PERFORMANCE

STANDARDS API SL / CF

Excellent performing anti-wear additives to reduce internal frictions and increasing engine life duration.
Adapted viscosity for all types of engines working under tropical conditions.
Lower oil consumption due to the low volatility.
Very efficient detergent power for a better engine cleanliness.
Maximum protection at high temperatures to avoid oxidation phenomenon.
Compatible with catalytic converters.
Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Drain period : according to manufacturers' recommendations and tune to your own use.
MOTUL MUTIPOWER 15W-50 can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	15W-50
Density at 15°C (59°F)	ASTM D4052	0.876
Viscosity at 100°C (212°F)	ASTM D445	18.4 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	137 mm ² /s
Viscosity index	ASTM D2270	150
Flash point	ASTM D92	237°C / 459°F
TBN	ASTM D4739	7.3 mg KOH/g