



PowerJet 4T 10W-40

4 Stroke engine oil for Jet Ski

Technosynthese®

TYPE OF USE

Specially designed for Jet Ski, Water Scooter, PWC – Personal Water Craft, Watercraft,... 4 Stroke marine engines, turbocharged or supercharged. Leisure or racing use.

Compatible with catalytic converters.

Suitable for all type of Gasoline fuels, leaded or unleaded, with or without Ethanol, biofuels.

PERFORMANCES

STANDARDS API SM / SL

PERFORMANCES JASO MA

The reinforced synthetic Technosynthese® base stock provides very high lubricating power which reduces frictions for higher power output and ensures resistance to very high temperatures reached in modern engines.

Outstanding detergent/dispersant properties avoiding sludge and deposits in the crankcase and maintaining engine cleanliness.

Protects against humid salt fog corrosion.

Anti-oxidation, Anti-wear, Anti-foam properties.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	10W-40
Density at 20°C (68°F)	ASTM D1298	0.870
Viscosity at 40°C (104°F)	ASTM D445	99.8 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.9 mm ² /s
Viscosity Index	ASTM D2270	152
Pour point	ASTM D97	-36°C / -33°F
Flash point	ASTM D92	227°C / 441°F
TBN	ASTM D2896	10.2 mg KOH/g