



Quad 4T 10W-40

Lubricant for 4 stroke ATV, VTT, Quad engine

TYPE OF USE

All 4 Stroke ATV, VTT, Quad engines with integrated or separated gearbox, for leisure or professional use. Particularly suitable for wet clutches.

PERFORMANCES

STANDARDS API SJ
 JASO MA - approval M033MOT104

JASO MA standard guarantees the perfect working of wet clutch and gearbox durability.
Formula especially reinforced with Extreme Pressure additives for gearbox.
High lubricating properties which decrease friction and wear and increase engine lifetime.
High detergent and dispersive properties.
Anti-oxidation, Anti-corrosion, Anti-foam.

RECOMMENDATIONS

Oil change: according to manufacturers' requirements and to be adjusted according to particular use.
Can be mixed with synthetic or mineral lubricants.

PROPERTIES

Viscosity grade	SAE J300	10W-40
Density at 20°C (68°F)	ASTM D1298	0.871
Viscosity at 40°C (104°F)	ASTM D445	100.8 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	15.2 mm ² /s
Viscosity Index	ASTM D2270	158
Flash point	ASTM D92	225°C / 437°F
Pour point	ASTM D97	-31°C / -23.8°F
TBN	ASTM D2896	6.7 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79. Web Site: www.motul.com

08/13