



SAE 15W-40

Gasoline and Diesel engine oil

Mineral

TYPE OF USE

Designed for the old generation of Gasoline and Diesel engines.

Suitable for all types of fuel (i.e. standard, unleaded, Diesel fuel, LPG) and with the use of catalytic converter.

All driving conditions: City, Road, Highway.

PERFORMANCE

STANDARDS

API SF / CD

Detergent and dispersing agents to keep the engine clean.

Efficient anti-wear additivation to increase engine's longevity.

Anti-oxidation properties.

Anticorrosion, Anti-foam properties.

RECOMMENDATIONS

Drain interval : according to manufacturers' requirements and adjust according to your own use.
MOTUL SAE 15W-40 can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	15W-40
Density at 20°C (68°F)	ASTM D1298	0.875
Viscosity at 100°C (212°F)	ASTM D445	14.5 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	110 mm ² /s
Viscosity Index	ASTM D2270	135
Pour point	ASTM D97	-27°C / -17°F
Flash point	ASTM D92	224°C / 435°F
TBN	ASTM D2896	10.2 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79 - Site Web : www.motul.fr

09/10