



MULTIPOWER PLUS 10W-40

Gasoline and Diesel Engine Oil

Technosynthèse^â

TYPE OF USE

Designed for recent passenger cars equipped with gasoline or diesel engines, turbo or naturally aspirated.

Suitable for standard and unleaded fuel.
All driving conditions : City, Road, Highway.

PERFORMANCE

STANDARDS API SM / CF

MULTIPOWER PLUS has been developed and tested in accordance with the latest performance specifications. It incorporates the latest lubricant technology to meet the current API SM performance.

The high performance anti-wear additive results in reduction of engine internal frictions and increases life duration by the wear reduction.

Excellent anti-oxidation preventing premature oil thickening and ageing due to thermal stress.

Very efficient anti-deposit and anti-black sludge power which maintains a clean engine.

Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Drain period : according to manufacturers' recommendations and tune to your own use.
MOTUL MUTIPOWER PLUS 10W-40 can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	10W-40
Density at 15°C (59°F)	ASTM D4052	0.863
Viscosity at 100°C (212°F)	ASTM D445	14.2 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	95.7 mm ² /s
Viscosity index	ASTM D2270	152
Pour point	ASTM D97	-39°C / -38°F
Flash point	ASTM D92	233°C / 451°F
TBN	ASTM D4739	6.3 mg KOH/g