



# Scooter Expert 2T

Lubricant for 2 Stroke Scooter engines

Technosynthese® – Anti-Smoke

## TYPE OF USE

All scooters daily used in town/city conditions.

Suitable for 2 Stroke engines, direct injection or conventional carburetor.

Can be used with oil injection systems or in premix.

Suitable for all type of gasoline fuels, leaded or unleaded, with or without Ethanol, biofuels.

Compatible with catalytic converters.

## PERFORMANCES

STANDARDS                      API TC  
  ISO-L-EGD

SPECIFICATIONS                JASO FD under N° 033MOT071

Synthetic Technosynthese® engine oil developed for scooter 2 Stroke engines running at high rpm. Reinforced with synthetic base stocks for outstanding oil film resistance and anti-wear protection. Avoid deposits and ensures engine cleanliness at all levels: combustion chamber, spark plug, piston top, ring grooves, exhaust port, exhaust pipe...etc.

## RECOMMENDATIONS

Mixing ratio: from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements.  
To be adjusted according to your own use.

## PROPERTIES

|                            |            |                         |
|----------------------------|------------|-------------------------|
| Color                      | Visual     | Green                   |
| Density at 20°C (68°F)     | ASTM D1298 | 0.857                   |
| Viscosity at 40°C (104°F)  | ASTM D445  | 65.2 mm <sup>2</sup> /s |
| Viscosity at 100°C (212°F) | ASTM D445  | 9.8 mm <sup>2</sup> /s  |
| Viscosity Index            | ASTM D2270 | 133                     |
| Flash point                | ASTM D92   | 144°C / 291°F           |
| TBN                        | ASTM D2896 | 0.97 mg KOH/g           |

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 Aubervilliers Cedex - BP 94 – FRANCE. Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79. Web Site: [www.motul.com](http://www.motul.com)

01/20