



Specific DiJet 2T

2 stroke biodegradable engine oil

SEADOO Jet Ski

100% Synthetic Ester – API TC

TYPE OF USE

For SEADOO 2 stroke engines of Jet lubricated in premix or by oil injector, also suitable for marine engines where manufacturer requires API TC lubricant.

Designed for leisure or racing, high performance 2 stroke engines fitted with Direct Injection or carburettors.

Designed for leaded or unleaded gasoline.

PERFORMANCE

STANDARDS: **API TC - JASO FC - ISO-L-EGD**
CEC L - 33 - A - 93 biodegradability test.

High performance oil : 100% synthetic ester base stock reduces frictions for higher power output.

Exceeds the API TC upper standard level, low smoke.

ISO-L-EGD tests are the most severe for detergency (30% more severe than JASO FC). Consequently it allows to reduce drastically internal engine fouling, piston ring sticking, piston and exhaust port deposits.

Environment friendly : vegetal ester base achieves 80% of biodegradability according to CEC L-33-A-93 standard.

Mixes instantaneously with gasoline and remains stable.

RECOMMENDATIONS

Mixing ratio: from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements. Adjust according to your own use.

PROPERTIES

Colours fuel in green.

Density at 20°C (68°F)	ASTM D1298	0.885
Viscosity at 100°C (212°F)	ASTM D445	7.4 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	36.5 mm ² /s
Viscosity index	ASTM D2270	174
Flash point	ASTM D92	124°C / 255°F
Pour point	ASTM D97	-45°C / -49°F
Biodegradability	CEC L-33-A-93	80%