



TEKMA NORMA

Lubricant for hydraulic systems and hydrostatic transmissions

Viscosity: SAE 10W monograde

TYPE OF USE

Suitable for hydraulic systems, torque converters and mechanical transmissions when an engine oil is recommended by manufacturers.

PERFORMANCES

STANDARDS : API **CF / SF**

SPECIFICATIONS : Zinc content > 900 ppm as required by **CATERPILLAR** for hydraulic systems.

Ensures engine protection and life time owing to piston groove deposits reduction.

High dispersant level : reduce soot build up and oil filter plugging risk.

Excellent bore polishing protection.

Anti-oxidation, Anti-corrosion, Anti-rust, Anti-foam.

RECOMMENDATIONS

Drain interval : refer to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J300	10W
Density at 20°C (68°F)	ASTM D1298	0.872
Viscosity at 40°C (104°F)	ASTM D445	31.9 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	5.4 mm ² /s
Viscosity Index	ASTM D2270	103
Flash point	ASTM D92	224°C / 435°F
Pour point	ASTM D97	-42°C / -44°F
TBN	ASTM D2896	10.1 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL, 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79. Web Site : www.motul.fr