



# TRAILUB

**Lubricant for Milking Machines  
Vacuum Pumps**

**Farm Machinery**

**SAE 15W-30**

## TYPE OF USE

**Specially formulated for lubrication of milking machines vacuum pumps.**  
All types of milking machines.

## PERFORMANCE

Highly resistant to oxidation, foaming and hydrolysis.  
Good desemulsifying properties.  
Anti-oxidation and anti-rust.  
Anti-corrosion and anti-wear.

## ADVANTAGES

Good working of the machines, even at low temperatures.  
Lasting quality of the vacuum pumps.

## PROPERTIES

Viscosity grade	SAE J 300	<b>15W-30</b>
Density at 20°C (68°F)	ASTM D1298	0.882
Viscosity at 40°C (104°F)	ASTM D445	69 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	10 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	128
Flash point	ASTM D92	240°C / 464°F
Drop point	ASTM D97	-18°C / 0°F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE.

MOTUL SA . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : (33 1) 48 11 70 00 - FAX : (33 1) 48 33 28 79 - TELEX MOTUL 235779F 09/10