



TRANSLUBE

Lubricant for Outboard Propeller Box

Anti-emulsion

TYPE OF USE

Anti-emulsion gearing oil, specially formulated to lubricate outboard propeller boxes:
EVINRUDE, FORCE, JOHNSON, MARIMER, MERCURY, SEAGULL, SELVA, TOHATSU, YAMAHA.

PERFORMANCES

Meets US STEEL 224 specification requirements.
High lubricating power to reduce frictions and wear.
Perceptibly reduces box working noise.
Extreme Pressure, anti-foam, anti-corrosion.
Good anti-emulsion properties.

RECOMMENDATIONS

Drain period: according to manufacturers' recommendations and to be adapted to your own use.
An oil drain once a year is recommended in any case.
Not to be used in electrical reverse gear system.

PROPERTIES

Viscosity grade	SAE J 300	90
Density at 20°C (68°F)	ASTM D1298	0.883
Viscosity at 40°C (104°F)	ASTM D445	143 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.7 mm ² /s
Viscosity Index	ASTM D2270	100
Flash point	ASTM D92	229°C / 444°F
Pour point	ASTM D97	-32°C / -26°F
Desemulsion	ASTM D2711	(free water) 47.6 ml
Emulsion		none