



# TP/AGRI GREASE

**Multipurpose Grease for Civil Engineering Machinery and Agriculture**

**Lithium – Very adherent & water resistant**

**NLGI 2 - Extreme-Pressure**

## TYPE OF USE

Multipurpose grease specially formulated for applications requiring a good resistance to heavy loads and to water which are conditions encountered in Civil Engineering and Agriculture.

Greasing of roller bearings, articulations, bearings, cables...

Tractors, Combine (Harvester), Wine Machinery and all kind of Civil Engineering Machinery.

Temperature for use : from -30°C / -22°F to +140°C / +284°F.

## PERFORMANCE

Grease with lithium soap reinforced by adhesive polymers and with extreme-pressure, anti-oxidation & anti-corrosion additivation.

### Advantages :

- Excellent results in presence of water.
- Good adherence on surfaces.
- Very good anti-wear & anti-corrosion protection.
- Good performance in time.
- Excellent results for heavy loads.

Designation DIN 51502 : KP 2 N-30

## PROPERTIES

Color	Visual	Green
Consistency grade	DIN 51 818	NLGI 2
Soap		Lithium
Penetrability - 60 cycles	ASTM D217	265 / 295 x10 <sup>-1</sup> mm
Drop point	ASTM D2265	190°C / 374°F
Anti-corrosion EMCOR	IP 220	0 / 0
TIMKEN Test - load	ASTM D 2509	50 lb
FAG FE-9 Test	DIN 51 821	F50 > 200 hr at 140°C (284 °F)

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel 33 1 48 11 70 00 - FAX 33 1 48 33 28 79 . Web Site: [www.motul.fr](http://www.motul.fr)

07/09