

**SAE 15W-50** 

# Technosynthèse<sup>®</sup>

### **TYPE OF USE**

All 4 stroke motorbike engines

Road and off road bikes, Trails, 4 stroke Cross/Enduro bikes, Quads, Scooters, Mopeds...

## **PERFORMANCE**

STANDARDS:

**API SL** JASO MA



JASO T 903 : 2006 PERFORMANCE GUARANTEED by MOTUI

JASO MA is a friction test for motorcycle 4 stroke engine oils which guarantees the perfect working of wet clutch and consequently the gearbox longevity.

Excellent anti-oxidation preventing premature oil thickening and ageing due to high temperature stress. High lubricating properties which decrease friction and wear and increase engine life. High detergent and dispersive properties.

Anti-corrosion, Anti-foam properties.

### RECOMMENDATIONS

Oil change: according to manufacturers' requirements and to be adjusted according to particular use. MOTUL 3100 Gold 4T can be mixed with synthetic or mineral lubricants.

#### **PROPERTIES**

Viscosity grade	SAE J 300	15W-50
Density at 15 °C (59 °F)	ASTM D1298	0.877
Viscosity at 100 °C (212 °F)	ASTM D445	18.3 mm <sup>2</sup> /s
Viscosity at 40 °C (104 °F)	ASTM D445	137.3 mm <sup>2</sup> /s
Viscosity index	ASTM D2270	150
Flash Point	ASTM D92	236
TBN	ASTM D2896	6.5 mg KOH/g