



SUBARU by MOTUL

5W-30

Petrol & Diesel engine oil - Euro 4, 5 et 6

100% Synthetic

TYPE OF USE

High performance 100% Synthetic Fuel Economy Engine Oil with reduced content of Sulfated Ash, Phosphorus and Sulfur ("Mid-SAPS") specially designed for all generation of SUBARU cars, including both Diesel and Petrol engines compliant to Euro 4, 5 and 6 emission regulation requesting the ACEA C2 standard in viscosity grade 5W-30.

Fulfils all SUBARU engineering and technical requirements to keep the engine genuine warranty. Suitable also for engines requiring engine oil with API SN, API SN-RC or ILSAC GF-5 standards, in 5W-30 viscosity grade.

Compatible with catalytic converters and Diesel Particulate Filters (DPF).

PERFORMANCES

STANDARDS

**ACEA C2
API SERVICE SN-RC
ILSAC GF-5**

SPECIFICATIONS



Genuine warranty coverage

The SUBARU recommendations require for the lubricant to be approved ACEA C2 in order to guarantee fuel economy benefit and perfect durability of SUBARU Petrol and Diesel engine ranges.

The API SN standard is fully backward compatible over API SM requirements and all former API standards. The API SN-RC "Resource Conserving" specification is even more demanding on the energy saving requirements.

API SN-RC lubricants provide outstanding oxidation resistance, better anti-deposits protection, better engine cleanliness, anti-wear protection and enhanced performance at cold temperature for Fuel Economy savings during the whole oil life span.

ACEA C2 lubricants are environment friendly and reduce fuel consumption, minimizing green house gases (CO₂) emission and also achieve extended drain intervals managed by vehicles on-board computer.

RECOMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.

Do not mix with non ACEA C2 compliant lubricants.

Before use always refer to the owner manual of the vehicle.

PROPERTIES

Viscosity grade	SAE J 300	5W-30
Density at 20°C (68°F)	ASTM D1298	0.840
Viscosity at 40°C (104°F)	ASTM D445	60.4 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	10.6 mm ² /s
HTHS viscosity at 150°C (302°F)	ASTM D4741	3.2 mPa.s
Viscosity index	ASTM D2270	169
Pour point	ASTM D97	-34°C / -29°F
Flash point	ASTM D92	231°C / 448°F
Sulfated ash	ASTM D874	0.48% weight
TBN	ASTM D2896	7.3 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 Aubervilliers Cedex - BP 94 - FRANCE. Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - Web site: www.motul.com

08/20