



# H-TECH Prime 5W-40

**Gasoline and Diesel Engine Lubricant**

**100% Synthetic**

## TYPE OF USE

Specially designed for new generation engines (gasoline, diesel, LPG, turbocharged and direct injection).

H-TECH Prime 5W-40 is recommended for cars requiring VW 502 00, 505 00 or MB-Approval 229.5 oils.

All driving conditions : City, Road, Highway.

## PERFORMANCE

STANDARDS	API SN/CF ACEA A3/B4
APPROVALS	VW 502 00, 505 00, MB-Approval 229.5

Has been developed to provide the following protection:

- Outstanding detergent and dispersant properties which meets the stringent ACEA B4 requirements.
- Superior anti-sludge and anti-wear performance to keep engine clean and protected.
- Advanced additive chemistry to provide excellent fuel economy.
- Excellent in meeting OEM extended drain targets.
- Anti-corrosion and anti-foam properties.

## RECOMENDATIONS

Drain interval : according to manufacturers' recommendations and tuned to your own use.  
MOTUL H-TECH Prime can be mixed with synthetic or mineral oils.

## PROPERTIES

Viscosity grade	SAE J 300	<b>5W-40</b>
Density at 15°C (68°F)	ASTM D4052	0.853
Viscosity at 40°C (104°F)	ASTM D445	85.1 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	14.0 mm <sup>2</sup> /s
Viscosity index	ASTM D2270	170
TBN	ASTM D2896	10.8 mg KOH/g