



3000 PLUS 4T 15W50

Lubricant for 4 Stroke motorcycle engine

HC-TECH[®] Technology

TYPE OF USE

Street & road bikes, trails, off-road bikes fitted with 4 stroke engines, integrated gearbox or not, wet or dry clutch, engines with or without catalytic converters.

Other users: Scooters, ATV, Mopeds...

PERFORMANCE

STANDARDS API SJ
APPROVAL JASO MA2 under M065MOT036

3000 PLUS 4T is based on HC-TECH[®] technology that provides excellent performance in lubricating properties – superior protection for engine & gearbox.

Specially formulated to provide lesser oil loss and better control on sludge formation.
Improved shear resistance to enhance gear protection & longer life of gears.
Performs well to minimize wear and increase engine life time.

JASO MA2 ensures the perfect clutch lock up at start-up, acceleration and full speed.
Easy gear shifting.

RECOMMENDATIONS

Oil change : follow the manufacturers' recommendations and to be adjusted according to the using condition. Can be mixed with synthetic or semi-synthetic lubricants.

PROPERTIES

Viscosity grade	SAE J 300	15W-50
Density at 20 °C (68 °F)	ASTM D1298	0.864
Viscosity at 40 °C (104 °F)	ASTM D445	141.5 mm ² /s
Viscosity at 100 °C (212 °F)	ASTM D445	17.8 mm ² /s
Viscosity index	ASTM D2270	139
Pour point	ASTM D97	-30 °C
Flash point	ASTM D92	238 °C
TBN	ASTM D 2896	4.5 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France
MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79. Web Site: www.motul.fr