



CLASSIC SAE 50

**4 Stroke Engine Oil
For Classic Cars and vehicles**

Mineral Monograde

TYPE OF USE

Mineral monograde lubricant especially formulated for Classic Gasoline or Diesel 4 stroke engines and transmissions built before 1950.

Specially designed for Ancestor, Veteran, Vintage, Prewar and Classic vehicles requiring a SAE 50 viscosity grade lubricant.

Modern version of classic monograde engine oil to perfectly suit requirement of climate conditions.

Easier start-ups for vehicles that are stored for long period of time.

Can also be used as break-in oil.

PERFORMANCE

MOTUL CLASSIC SAE 50 is a modern technology lubricant specially designed for old engines design and formulated with a high-Zinc level (ZDDP content above 1800 ppm) to provide the best anti-wear protection for your classic engine (genuine or rebuilt).

Mineral monograde lubricant with very low detergent level in order to be harmless with paper, felt and fabric gaskets from that period.

The low detergent level avoids soot and deposits removals in the lubricating circuit.

Compatible with "yellow" nonferrous metals as brass, bronze and copper.

Developed in the right viscosity grade to avoid oil leakages in classic vehicles and to maintain a consistent oil pressure and to reduce oil consumption.

Can be used as break-in oil if drain intervals are shortened.

Reinforced adherence for easier start even after a long period of immobilization.

RECOMMENDATIONS

Drain interval: drain at least once a year.

PROPERTIES

Viscosity grade	SAE J 300	50
Density at 20°C (68°F)	ASTM D1298	0.898
Viscosity at 40°C (104°F)	ASTM D445	255.2 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	21.0 mm ² /s
Viscosity index	ASTM D2270	97
Pour point	ASTM D97	-27°C / -17°F
Flash point	ASTM D92	258°C / 496°F
TBN	ASTM D2896	1.7 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Boulevard Félix Faure - 93303 Aubervilliers Cedex - BP 94 - FRANCE. Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - Web Site: www.motul.com

01/21