



H-TECH 100 5W-30

Gasoline and Diesel Engine Oil

100% Synthetic

TYPE OF USE

Designed for use in turbocharged or naturally aspirated gasoline engines. Can also be used on diesel engines requiring API CF oils.

Suitable for standard leaded or unleaded gasoline, LPG or Autogas fuel.
All driving conditions : City, Road, Highway.

PERFORMANCE

STANDARDS API SM
 with CF performance

Formulated with high performance additives to provide enhanced stability to oxidation which prevents oil thickening and sludge formation problems. Outstanding anti-wear properties for better engine wear protection.

5W-30 viscosity grade provides smooth engine start under cold climate and improved fuel economy.

RECOMENDATIONS

Drain interval : according to manufacturers' recommendations and tuned to your own use.

MOTUL H-TECH 100 can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	5W-30
Density at 15°C (68°F)	ASTM D4052	0.852
Viscosity at 40°C (104°F)	ASTM D445	66.4 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	11.1 mm ² /s
Viscosity index	ASTM D2270	159
TBN	ASTM D2896	7.8 mg KOH/g