



MULTIPOWER 20W-50

Gasoline and Diesel Engine Oil

Technosynthese®

TYPE OF USE

Designed for passenger cars equipped with gasoline or diesel engines, turbo or naturally aspirated.

Suitable for standard and unleaded fuel.

All driving conditions : City, Road, Highway.

PERFORMANCE

STANDARDS API SM with CF performance

Specifically created with adapted viscosity for all types of engines working under tropical conditions. Provides maximum engine protection and exceptional low oil consumption at high temperatures, even to older vehicles. Excellent anti-oxidation properties to prevent premature oil thickening. Keeps engine clean and prolongs engine life. Good anti-corrosion and anti-foam properties.

RECOMENDATIONS

Drain period : according to manufacturers' recommendations and tune to your own use.
MOTUL MUTIPOWER 20W-50 can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	20W-50
Density at 20°C (68°F)	ASTM D4052	0.867
Viscosity at 40°C (104°F)	ASTM D445	150.7 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	17.6 mm ² /s
Viscosity index	ASTM D2270	128
TBN	ASTM D2896	7.2 mg KOH/g