



SCOOTER POWER LE 5W-40

**High performance lubricant for 4 stroke
engineoil Scooters**

100% Synthetic – Low Emission

TYPE OF USE

High performance motor oil designed to meet today's 4 stroke engines for powerful and recent scooters for which manufacturers recommends JASO MB specification. It provides effective control of piston deposit, wear and bearing corrosion.

All driving conditions : City road, Highway.

ATTENTION : Not suitable for 4T motorcycle engine.

PERFORMANCE

STANDARD API SL
APPROVAL JASO MB under N° M065MOT010

100% Synthetic lubricant for improved oil film resistance at high temperatures and high revolutions. JASO MB approval ensure perfect operating conditions when a dry clutch is fitted on the scooter. The SAE 5W-40 viscosity grade corresponds to most recent manufacturers' recommendations and improves engine starts when cold while lowering wear. Very low volatility to reduce oil consumption. Superior low emission control. Outstanding engine cleanliness, detergent and dispersives properties. Maintain oxidation stability and reduce soot accumulation. Resistance to corrosion and foaming.

RECOMENDATIONS

Drain interval : according to manufacturers' recommendations and tune to your own use.
MOTUL Scooter Power LE 5W-40 cannot apply to the system that requires JASO MA specification.

PROPERTIES

| | | |
|----------------------------|-------------|-------------------------|
| Viscosity grade | SAE J 300 | 5W-40 |
| Density at 15°C (59°F) | ASTM D1298 | 0,856 |
| Viscosity at 100°C (212°F) | ASTM D445 | 14.2 mm ² /s |
| Viscosity at 40°C (104°F) | ASTM D445 | 81.1 mm ² /s |
| Viscosity index | ASTM D2270 | 181 |
| Pour point | ASTM D97 | -33°C / -27°F |
| Flash point | ASTM D92 | 226°C / 428°F |
| TBN | ASTM D 2896 | 7.2 mg KOH/g |