



ATV POWER 4T 5W-40

High performance lubricant for ATVs

100% Synthetic - Ester

TYPE OF USE

ATV - All-Terrain Vehicles, quads... sporty or urban, fitted with 4 Stroke engines, integrated gearbox or not, wet or dry clutch, engines meeting Euro 2, 3, 4 or 5 emission regulation, fitted with exhaust gas after treatment systems: catalytic converters, air injection into exhaust pipe...

ATVs, quads... used for leisure and recreation.

Suitable for all type of gasoline fuels, leaded or unleaded, with or without Ethanol, biofuels.

PERFORMANCE

STANDARDS API SN / SM / SL / SJ
SPECIFICATIONS JASO MA2 under N° M033MOT173

100% Synthetic - Ester lubricant for improved oil film resistance at high temperatures.

Formula reinforced with Ester and anti-wear additives for improved oil film shear resistance and for increased gear protection and life time duration.

The JASO MA2 approval guarantees the efficient high friction level to secure the clutch engagement during the three riding modes: Starting, Acceleration and Constant Speed.

Optimized Phosphorus and Sulfur contents for better operating conditions of catalytic converters required to meet latest emission regulations.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral lubricants.

PROPERTIES

Color	Visual	Red
Viscosity grade	SAE J 300	5W-40
Density at 20°C (68°F)	ASTM D1298	0.855
Viscosity at 40°C (104°F)	ASTM D445	79.2 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	13.6 mm ² /s
Viscosity index	ASTM D2270	172
Pour point	ASTM D97	-35°C / -31°F
Flash point	ASTM D92	224°C / 435°F
TBN	ASTM D2896	8.3 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 Aubervilliers Cedex - BP 94 - FRANCE. Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79. Web Site: www.motul.com

01/20