



# 100 2T

**Lubricant for 2 Stroke engines**

**Lubrication by oil injector or premix**

## TYPE OF USE

Any 2-Stroke bike, trails, off road bikes, mopeds... fitted with small displacement 2 stroke engines.  
Suitable for oil injector systems or premix, leaded or unleaded gasoline

## PERFORMANCE

STANDARDS                      API TC  
SPECIFICATIONS                JASO FB level

Lubricant suitable for all kind of injection systems.  
Minimise deposits on engine internal components and exhaust pipes.  
Prevents spark plug from fouling.

Instantaneous and stable mixing with gasoline.

## RECOMMENDATIONS

Premix ratio: from 3% to 4% (from 33:1 to 25:1) according to manufacturers' requirements.  
Adjust according to your own use.

## PROPERTIES

Colour	Visual	Green
Density at 20°C (68°F)	ASTM D1298	0.879
Viscosity at 40°C (104°F)	ASTM D445	77.9 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	9.9 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	107
Flash point	ASTM D92	166°C / 330.8°F
Pour point	ASTM D97	-15°C / -5°F
TBN	ASTM D2896	1.2 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. - Made in France

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79. Site Web : [www.motul.com](http://www.motul.com)

07/15