



# TRANSOIL 10W-30

Lubricant for gearboxes with wet clutch

**Mineral**

## TYPE OF USE

Specially formulated for gearboxes with wet clutch using different oil from the engine oil: gearbox case separated from engine crankcase.

All type of Motorbikes: Road, Trails, Cross (2 or 4 Stroke engine), Enduro (2 or 4 Stroke engine), Mopeds, Scooters, Quads, ATV, UTV...

Suitable when manufacturers require for the transmission an SAE 10W-30 engine oil or SAE 80 gearbox oil.

## PERFORMANCE

Easy gear shift.

High oil film resistance for gear protection.

Avoid clutch slippage for better transmission efficiency.

Dispersant properties to maintain clutch discs clean.

Extreme Pressure, Anti-wear, Anti-corrosion, Anti-foam.

## RECOMMENDATIONS

Oil change: According to manufacturers' requirements and to adjust according to your own use.

## PROPERTIES

Viscosity grade	SAE J 300	<b>10W-30</b>
Density at 20°C (68°F)	ASTM D1298	0.871
Viscosity at 40°C (104°F)	ASTM D445	78.7 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	12.0 mm <sup>2</sup> /s
Viscosity index	ASTM D2270	148
Flash point	ASTM D92	228°C / 442.4°F
Pour point	ASTM D97	-30°C / -22°F