



# Scooter Expert LE 10W30

Oil for 4 stroke motorcycle engine

SAE 10W-30

Technosynthese®

## TYPE OF USE

Specifically designed for 4 stroke engine of powerful and recent scooters for which manufacturer recommends JASO MB specification.

## PERFORMANCE

STANDARDS	API SL
APPROVAL	JASO MB under N° M065MOT026

Formulation is perfectly balanced to provide excellent control of piston deposit, wear and bearing corrosion. Good detergency to help maintain engine cleanliness. Good anti-oxidation properties to prevent premature ageing of oil.

SAE 10W-30 viscosity grade improves cold engine start and contributes to fuel economy.

## RECOMMENDATIONS

Oil change : according to manufacturers' recommendations and to be adjusted according to particular use. Can be mixed with synthetic or mineral lubricants.

MOTUL Scooter Expert LE 10W-30 can't be used to the system that requires JASO MA specification.

## PROPERTIES

Viscosity grade	SAE J 300	<b>10W-30</b>
Density at 15 °C (59 °F)	ASTM D1298	0.868
Viscosity at 40 °C (104 °F)	ASTM D445	72.8 mm <sup>2</sup> /s
Viscosity at 100 °C (212 °F)	ASTM D445	10.8 mm <sup>2</sup> /s
Viscosity index	ASTM D2270	136
Pour point	ASTM D97	-36 °C
Flash point	ASTM D92	226 °C
TBN	ASTM D 2896	7.4 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France  
MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79. Web Site: [www.motul.fr](http://www.motul.fr)