



# TWIN PRIMARY CHAINCASE OIL

High Performance TWIN Motorcycle Primary Chaincase Oil

100% Synthetic – Ester / PAO / GRP3

## TYPE OF USE

High performance 100% TRIPLE synthetic oil specially engineered to handle the combined duties of protecting the primary drive (Wet clutch, basket, sprockets and Chain)  
Recommended for Harley-Davidson® BIG TWINS

## PERFORMANCE

STANDARDS                      API SL  
SPECIFICATIONS              JASO MA2 tested

## PROTECTION

Ester Technology:

100% Triple synthetic extreme pressure lubricant for maximum anti-wear protection, better high temperature resistance, and extended life of the drive.

- Molecular polar bonding technology enables oil to cling to ferrous metal parts, providing a protective film to help reduce wear and corrosion.
- Advanced Ester formulation is used to minimize gear internal friction losses, reduces wear and extends the life of wet clutch, bearings, chains and sprockets.
- Reduces clutch drag and provides quieter smoother shifting, while providing outstanding grip for wet clutches, helping to prevent slippage and chatter.

**TWIN PRIMARY CHAINCASE OIL** provides outstanding oil film resistance at very hot temperatures which helps provides a more stable clutch while engaging and disengaging.

Better oil flow at low temperatures provides easier gear shifting and reduces the big CLUNK when the Drive components are cold.

Less effort required on the gear lever to shift the gears.

Anti-corrosion, Anti-foam, special detergents

## RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral lubricants in an emergency. The resulting diluted mixture will not perform as well and should be changed as soon as possible.

## PROPERTIES

Color	Visual	Yellow / Gold
Viscosity grade	SAE J 306	<b>10W40 (85W)</b>
Density at 20°C (68°F)	ASTM D1298	0.8504
Viscosity at 40°C (104°F)	ASTM D445	98.6 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	15.5 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	167
Pour point	ASTM D97	-24°C / -11.2°F
Flash point	ASTM D92	208°C / 406.4°F
TBN	ASTM D2896	6.5 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – **Made in USA**

MOTUL USA - 5836 Corporate Ave. Ste 150 – Cypress CA 90630 - Tel : 909-625-1292 - Fax : 909-625-2697 Website: [www.motul.com](http://www.motul.com)