



MULTI GREASE 200

High Performance Multipurpose Grease

Lithium

NLGI 2 – Extreme Pressure

TYPE OF USE

High performance multipurpose grease recommended for the lubrication of roller bearings, plain bearings, thrust bearings, gears, electric motors, winches, bushings, wheel bearings, universal joints, ball joints, chassis lubrication in heavy- and light-duty, automobiles, landscaping, agricultural, motorcycle and powersports equipment operating under normal to severe conditions.

Operating temperatures for long-term lubrication: from -20°C / -4°F to +130°C / +266°F.

PERFORMANCE

High quality multipurpose grease formulated with mineral base oil stock, lithium soap and Extreme Pressure, anti-wear, anti-oxidation & anti-corrosion additives.

Protect against corrosion

High pressure load capacity according to FAG FE-9 test

Water resistance with reinforced adhesiveness

Designation DIN 51502: KP 2 K-20

PROPERTIES

Color	Visual	Orange
Consistency grade	DIN 51 818	NLGI 2
Soap	Type	Lithium
Base oil viscosity at 40°C	DIN 51 562	180 mm ² /s
Base oil viscosity at 100°C	DIN 51 562	13 mm ² /s
Drop point	DIN 21 76	> 190°C
Penetrability - 60 cycles	ASTM D 217	265 / 295 x10 ⁻¹ mm
FAG FE-9 Test	DIN 51 821	F50 > 100 hr at 130°C (266°F)
Timken test	ASTM D 25 09	178 Nm
Four ball weld load test	DIN 51 350 T4	3400 N
Copper corrosion test	ASTM D 4048	1 / 100
Water Washout	DIN 51 807 T1	1 / 90