



MOTUL 200 4TR/S 10W-40

Lubricant for 4 stroke motorcycle engine

100% Synthetic

TYPE OF USE

All 4 stroke on and off road bikes, quads, scooters and mopeds.

PERFORMANCE

STANDARDS API SN
APPROVAL JASO MA2

Specially formulated to provide an excellent anti-oxidation property to protect crankcase, transmission and gearbox systems by preventing oil thickening and ageing due to thermal stress.
High detergent and dispersive properties for excellent engine cleanliness.
Performs well to minimize wear and increase engine life time.

JASO MA2 approved to ensure perfect operating conditions for wet clutches.

RECOMMENDATIONS

Oil change : according to manufacturers' recommendations and to be adjusted according to using conditions.

PROPERTIES

Viscosity grade	SAE J 300	10W-40
Density at 20°C (68°F)	ASTM D1298	0.852
Viscosity at 40°C (104°F)	ASTM D445	95.7 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.9 mm ² /s
Viscosity index	ASTM D2270	163
Pour point	ASTM D97	-33°C
Flash point	ASTM D92	228°C
TBN	ASTM D 2896	8.0 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79. Web Site: www.motul.fr

07/20